AN EVALUATION OF PRESENTATION ATTACK DETECTION OF FINGERPRINT BIOMETRIC SYSTEMS APPLYING ISO/IEC 30107-3

Ines Goicoechea-Telleria, Belen Fernandez-Saavedra, Judith Liu-Jimenez, Raul Sanchez-Reillo

Carlos III University of Madrid, Spain





Outline

- Why, how, what was done?
- Experiment
- Applying ISO/IEC JTC1 30107-3 to the experiment
- Results reporting
- Lessons learned

Outline


- Why, how, what was done?
- Experiment
- Applying ISO/IEC JTC1 30107-3 to the experiment
- Results reporting
- Lessons learned

Why, how, what was done?

WHY?

iPhone 5S fingerprint sensor hacked by Germany's Chaos Computer Club

Biometrics are not safe, says famous hacker team who provide video showing how they could use a fake fingerprint to bypass phone's security lockscreen



HOW?

Security evaluations (PAD)

ISO/IEC 30107-3 + Common Criteria

WHAT?

Find vulnerabilities \rightarrow experiment

Apply ISO/IEC 30107-3

Outline

- Why, how, what was done?
- Experiment
- Applying ISO/IEC JTC1 30107-3 to the experiment
- Results reporting
- Lessons learned














Experiment

- 4 sensors: 1 thermal, 2 capacitive, 1 optical
- 330 + 126 artefacts
- 36 real fingers, 6 capture subjects
- 4672 images
- Cooperative and non-cooperative attacks
- 10 artefact species: Play-Doh (x2), gelatine, latex, silicone, white glue, latex with graphite (x2), silicone with graphite (x2)

Experiment


Acquisition process

■ If sensors respond → more artefacts



Experiment

Classification of artefact species



Outline

- Why, how, what was done?
- Experiment
- Applying ISO/IEC JTC1 30107-3 to the experiment
- Results reporting
- Lessons learned











After

Applying ISO/IEC JTC1 – 30107-3

Artefacts

- Biometric impostor attacks
- Artefacts appear natural
- Extractable features




Select adequate materials for artefact species

- Separation cooperative/non-cooperative attacks
- Attacker's expertise

Applying ISO/IEC JTC1 – 30107-3 Process-dependent evaluation factors


- Enrolment
- Quality thresholds
- Presentation policy (operator oversight)
- Verification
- Usually no operator oversight
- In this case -> no quality threshold

Applying ISO/IEC JTC1 – 30107-3 Attack Potential




Applying ISO/IEC JTC1 - 30107-3


Attack Potential



Applying ISO/IEC JTC1 - 30107-3

Level of evaluator's access





Applying ISO/IEC JTC1 – 30107-3 Metrics

Attack Presentation Non-Response Rate

Data capture APNRR = AP that cause no response/total AP

Attack Presentation Non-Capture Rate

APNCR = AP with low quality/total AP

Attack Presentation Match Rate

APMR= AP that match reference/total AP

Attack Presentation Non-Match Rate

APNMR= *AP that do not match reference/*total *AP*

Applying ISO/IEC JTC1 - 30107-3

Required reporting metrics

System	Metric	Presentation type	Reported?					
	APCER	Attack	- no access to PAD subsystem					
Data capture	BPCER	Bona fide	* - no access					
subsystem	APNRR	Attack	✓					
	BPNRR	Bona fide	x - no access					
	APNCR	Attack	✓					
	FNMR/FMR	Bona fide	* - no access					
Comparison	APMR	Attack	✓					
subsystem (verification)	Full system processing duration	Attack or bona fide	Z – capture and verification done separately					

Applying ISO/IEC JTC1 - 30107-3

Other reporting metrics


Item		Va	lue		Comments					
Capture subjects	6				4 male, 2 female					
Sources for artefacts	36				Index, middle finger and thumb from both hands					
Artefacts	330 + 126				Not included in 30107-3, addition by the evaluator. Thermal and capacitive + optical.					
Artefact species	10				Silicone, silicone with graphite (mixed and on surface), latex, latex with graphite (mixed and on surface), Play-Doh (fresh and a bit dry), gelatine, latex and white glue					
Artefact series			-		Out of each mold one artefact was made for each species					
Detected AP (total, by capture subject, by artefact species, by artefact series)	*	-	*	-	* Reported later					
Non-detected AP (total, by capture subject, by artefact species, by artefact series)	*	-	*	-	* Reported later					
Detected normal presentations			_		Not reported – additional evaluation needed					
Non-detected normal presentations			-		Not reported – additional evaluation needed					
Alterations/modifications to artefact creation			-		There were no alterations to artefact creation. A different evaluation should be performed for this end.					
Configuration of PAD systems under test	NBIS, threshold = 25				Set from previous performance evaluation, same sensors					
Presentation attack resistance	Reported before									
Attack potential	Reported before									
Description of IUT (sensors)	1 th	erm., 2	cap., 1	opt.	Manufacturers and models are confidential					

Outline


- Why, how, what was done?
- Experiment
- Applying ISO/IEC JTC1 30107-3 to the experiment
- Results reporting
- Lessons learned


Attack Presentations = rejected artefacts + accepted artefacts

APNRR + APNCR + APNMR APMR





Cooperative attacks





(All) Cooperative attacks







Cooperative attacks


	Silicone				Gelatine			Latex			Latex + graphite				Latex + graphite surface					
Sensor	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt
Artef		6		6		36		30		12		30		12		6		36		12
AP	25	36	36	6	114	130	102	32	47	72	72	31	52	72	72	6	108	214	190	36
Resp	25	24	0	6	114	130	62	28	47	66	0	29	52	72	0	6	101	156	4	0
NFIQ>3	17	36	36	1	95	120	82	7	29	72	72	2	39	72	72	3	59	212	189	36
APNRR	0%	33%	100%	0%	0%	0%	39%	13%	0%	8%	100%	6%	0%	0%	100%	0%	6%	27%	98%	100%
APNCR	68%	67%	0%	17%	83%	92%	41%	9%	62%	92%	0%	0%	75%	100%	0%	50%	48%	72%	2%	0%
APNMR	24%	0%	0%	50%	15%	8%	16%	50%	32%	0%	0%	94%	25%	0%	0%	33%	41%	1%	1%	0%
APMR	8%	0%	0%	33%	2%	0%	4%	28%	6%	0%	0%	0%	0%	0%	0%	17%	5%	0%	0%	0%
	S	ilicone	+ graphi	te	Silicone + graphite surface			Play-Doh			Play-Doh after 30 minutes			White glue						
Sensor	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt	Ther	Cap1	Cap2	Opt
Artef		12		6		12		6		42		30		12		0		6		0
AP	37	66	96	36	24	34	33	36	126	247	181	30	27	97	56	-	20	33	36	-
Resp	23	60	0	5	24	24	0	0	124	205	110	21	27	65	26	-	20	33	0	-
NFIQ>3	22	66	96	31	17	33	33	36	72	239	161	10	4	95	39	-	10	30	36	-
APNRR	38%	9%	100%	86%	0%	29%	100%	100%	2%	17%	39%	30%	0%	33%	54%	-	0%	0 %	100%	-
APNCR	22%	91%	0%	0%	71%	68%	0%	0%	56%	80%	50%	3%	15%	65%	16%	-	50%	91%	0%	-
APNMR	24%	0%	0%	8%	17%	3%	0%	0%	40%	0%	8%	40%	74%	1%	23%		30%	9%	0%	
APMR	16%	0%	0%	6%	13%	0%	0%	0%	3%	3%	3%	27%	11%	1%	7%	-	20%	0%	0%	-


Non-cooperative attacks





(All) Non-cooperative attacks





Non-cooperative attacks

		Silicone		Gelatine				Latex		Latex + graphite			
Sensor	Ther	Cap1	Cap2	Ther	Cap1	Cap2	Ther	Cap1	Cap2	Ther	Cap1	Cap2	Γ
Artef.		24			30			24			6		
AP	110	138	174	161	218	196	104	142	144	36	32	36	
Resp.	106	138	0	136	206	73	100	142	0	0	32	0	
NFIQ > 3	90	138	174	123	209	179	79	141	144	36	30	36	
APNRR	4%	0%	100%	16%	6%	63%	4%	0%	100%	100%	0%	100%	
APNCR	78%	100%	0%	61%	90%	29%	72%	99%	0%	0%	94%	0%	
APNMR	17%	0%	0%	24%	4%	9%	22%	1%	0%	0%	6%	0%	
APMR	1%	0%	0%	0%	0%	0%	2%	0%	0%	0%	0%	0%	
	Silic	one + grap	ohite	Silicone + graphite surface			Play-Doh			White glue			
Sensor	Ther	Cap1	Cap2	Ther	Cap1	Cap2	Ther	Cap1	Cap2	Ther	Cap1	Cap2	
Artef.		6		24			18			6			
AP	36	36	36	139	144	144	77	107	107	23	36	36	
Resp.	0	36	0	124	132	0	77	93	7	19	36	0	
NFIQ > 3	36	36	36	135	143	144	60	101	107	17	35	36	
APNRR	100%	0%	100%	11%	8%	100%	0%	13%	93%	17%	0%	100%	
APNCR	0%	100%	0%	86%	91%	0%	78%	81%	7%	57%	97%	0%	
APNMR	0%	0%	0%	3%	1%	0%	21%	6%	0%	26%	3%	0%	
APMR	0%	0%	0%	0%	0%	0%	1%	0%	0%	0%	0%	0%	

Latex + graphite surface

Cap1

36

100%

0%

100%

0%

Cap2

36

0

100%

0%

0%

0%

Outline

- Why, how, what was done?
- Experiment
- Applying ISO/IEC JTC1 30107-3 to the experiment
- Results reporting
- Lessons learned

Lessons learned

- Compare security evaluations
- Attack Potential difficult to measure, should be more specific
- 2 side-by-side graphs (rates, quantities)
- Environmental conditions should be reported
- Give image examples of artefacts and captured samples

References

- ISO / IECJTC 1 / SC37, "CD 30107-3, Biometric presentation attack detection Part 3: Testing and reporting," 2016.
- Common Criteria, "Common Methodology for Information Technology Security Evaluation methodology September 2012 Revision 4 Foreword," *Ccmb-2012-09-004*, no. September, p. 433, 2012.
- T. van der Putte and J. Keuning, "Biometrical fingerprint recognition: don't get your fingers burned," Smart card Res. Adv. Appl. IFIP TC8/WG8. 8 Fourth Work. Conf. Smart Card Res. Adv. Appl. Sept. 20-22, 2000, Bristol, United Kingdom, vol. 31, no. 0, p. 16, 2000.
- L. Thalheim, J. Krissler, and P.-M. Ziegler, "Body Check: Biometrics Defeated," 2002. [Online]. Available: http://www.pcmag.com/article2/0,2817,13919,00.asp.
- S. a C. Schuckers, "Spoofing and Anti-Spoofing Measures," *Inf. Secur. Tech. Rep.*, vol. 7, no. 4, pp. 56–62, 2002.
- J. Galbally, J. Fierrez, J. Rodriguez-Gonzalez, F. Alonso-Fernández, J. Ortega-Garcia, and M. Tapiador, "On the Vulnerability of Fingerprint Verification Systems to Fake Fingerprints Attacks," 2006.
- A. Choiniere and T. Lubysheva, *Novetta Protecting against Fingerprint Vulnerabilities when Deploying Biometric Systems*. 2015.

Thank you!

Extra info

Material	Elapsed time	Specialist Expertise	Knowledge of TOE	Window of opportunity	Equipment	Total	Attack potential	Attack resistance
Play-Doh	0	0	0	1	4	5	Basic	No rating
Play-Doh 30'	0	0	0	1	4	5	Basic	No rating
Gelatin	0	0	0	1	4	5	Basic	No rating
Silicone mixed with graphite	0	0	0	1	4	5	Basic	No rating
Silicone with graphite on surface	0	0	0	1	4	5	Basic	No rating
Latex mixed with graphite	1	0	0	1	4	6	Basic	No rating
Latex with graphite on surface	1	0	0	1	4	6	Basic	No rating
Latex	1	0	0	1	4	6	Basic	No rating
White glue	1	0	0	1	4	6	Basic	No rating
Silicone	0	0	0	1	4	5	Basic	No rating

Extra info

Enrolment process

